

Article overview

Barbecue coolers / lounge tables

Barbecue coolers



Product name	BBQ-Cooler S-R	BBQ-Cooler S-L	BBQ-Cooler Black S-R	BBQ-Cooler Black S-L	BBQ Cooler M-R	BBQ Cooler M-L
Item	700	701	702	703	696	697
EAN	40 38437 00700 8	40 38437 00701 5	40 38437 00702 2	40 38437 00703 9	40 38437 00696 4	40 38437 00697 1
Housing / colour	Stainless steel	Stainless steel	Stainless steel black	Stainless steel black	Stainless steel	Stainless steel
Door hinge	On the right	On the left	On the right	On the left	On the right	On the right
Temperature range**	2 - 14 °C	2 - 14 °C	2 - 14 °C	2 - 14 °C	-1 - 10 °C	-1 - 10 °C
Temperature zones	1	1	1	1	1	1
Cooling technology	Compressor	Compressor	Compressor	Compressor	Compressor	Compressor
Storage capacity	63 l	63 l	63 l	63 l	125 l	190 l
Shelves	4	4	4	4	4	4
IPX-4 (splash water protection)	■	■	■	■	■	■
UV filter glass	■	■	■	■	■	■
Interior lighting	LED	LED	LED	LED	LED	LED
Energy efficiency class	F	F	F	F	B	B
Annual consumption	99 kWh/a	99 kWh/a	99 kWh/a	99 kWh/a	584 kWh/a**	657 kWh/a**
Power	0,4 A	0,4 A	0,4 A	0,4 A	0,6 A	0,6 A
Voltage	220 V - 240 V; 50 Hz	220 V - 240 V; 50 Hz	220 V - 240 V; 50 Hz	220 V - 240 V; 50 Hz	220 V - 240 V; 50 Hz	220 V - 240 V; 50 Hz
Measures (WxHxD)	430 x 675 x 555 mm	430 x 675 x 555 mm	430 x 680 x 550 mm	430 x 680 x 550 mm	395 x 1025 x 650 mm	595 x 1025 x 650 mm
Weight	35 kg	35 kg	35,15 kg	35,15 kg	44,1 kg	59,5 kg
Certification	CE, GS	CE, GS	CE, GS	CE, GS	CE, GS	CE, GS
Packing unit	1	1	1	1	1	1

Barbecue Cooler



Product name	Counter & Cool	Steel trolley (without cooler)	Barbecue Cooler R	Barbecue Cooler L
Item	681	682	680	683
EAN	40 38437 00681 0	40 38437 00682 7	40 38437 00680 3	40 38437 00683 4
Housing / colour	Stainless steel	Stainless steel	Stainless steel	Stainless steel
Door hinge	On the right		On the right	On the left
Temperature range**	0 - 10 °C		0 - 10 °C	0 - 10 °C
Temperature zones	1		1	1
Cooling technology	Compressor		Compressor	Compressor
Storage capacity	63 l		63 l	63 l
IPX-4 (splash water protection)	▪		▪	▪
UV filter glass	▪		▪	▪
Interior lighting	LED		LED	LED
Energy efficiency class	F		F	F
Annual consumption	99 kWh/a		99 kWh/a	99 kWh/a
Power	60 Watt		60 Watt	60 Watt
Voltage	220 V - 240 V; 50 Hz		220 V - 240 V; 50 Hz	220 V - 240 V; 50 Hz
Measures (WxHxD)	1010 x 985 x 620 mm	1010 x 985 x 620 mm	430 x 690 x 540 mm	430 x 690 x 540 mm
Weight	59,2 kg	27,8 kg	31,4 kg	31,4 kg
Certification	CE, GS		CE, GS	CE, GS
Packing unit	1	1	1	1

*Bottle size based on a standard Bordeaux bottle (max. Ø 75 mm)

** The achievable value in the interior can not exceed the ambient temperature at the installation site